





PRODUCT INFO

BACK-ROLLER CITY

Rear pannier pair with roll closure and QL1 system



Carrying handle for mounting and releasing the QL1 system

D-ring for shoulder strap (optional)

Buckles for closing the rolling closure

Lateral 3M Scotchlite reflector on both sides

QL1 bar and hooks for quick fastening and release



Semi-elliptical hook rail with QL hook (adjustable in 15° steps)

Edge protector with slots for mounting the Carrying System Bike Pannier

Height cm/in	Width cm/in	Depth cm/in	Volume L/cu.in.	Weight g/oz.
42/16.5	23/32 9/12.6	17/6.7	40/2441 (pair)	1520/53.6 (pair)

SPECIFICATIONS:

- + Waterproof bike pannier (pair) ideal as starter model
- + QL1 mounting system with straight lower hook rail
- + Sides of PS 490 nylon material, front and back of PD620 material
- + No mounting required (simply adjust the hook distance with allen key no. 3)
- + Ideal for racks with a cross-section up to 16mm
- + Reduction pieces for rack cross-sections 8 and 11mm included
- + Can be used individually (e.g. for shopping, sports, picnic)
- + Highly reflective Scotchlite reflector
- + Can be easily cleaned inside
- + Easy to clean inside

Contents: Panniers come as a pair

Optional accessories: Packing Cubes/Commuter Insert for Panniers, Carrying System Bike Pannier, shoulder strap (No. E172)

Attention: Maximum load per pannier is 9kg / 20 lbs. We recommend weighing each loaded pannier to confirm that the maximum allowance of the pannier fixation is not exceeded. This practice is advised for both rear and front panniers. CAUTION: The maximum weight capacity of every carrier model is different. Please observe the maximum weight allowance of the carrier fitted to your bicycle. Note: Sometimes the maximum capacity of the panniers fixing system can exceed the maximum capacity of the carrier. DO NOT exceed the maximum capacity of the carrier! Note, that the use of panniers will significantly influence the handling properties of your bicycle.

Attention: As abrasion cannot be ruled out, we recommend that all points where the mounting system contacts the bicycle rack or frame be protected by scratch protection film.

Note: In order to meet standard IP64 (6=dustproof 4=protected against splash water coming from all directions) the lid must be rolled 3-4 times.